



6865 Vineland Ave., North Hollywood, CA 91605,

CONVERSION: 110V TO 220V (Reverse Procedure for 220V to 110V)

THE TRANSFORMER IS DUAL WOUND AND A SIMPLE PROCEDURE OF CHANGING PLACEMENT OF 2 WIRLS AT CONNECTOR WILL CHANGE VOLTAGE AND IS REVERSIBLE:





INSTRUCTIONS:
"REMOVE WH/BLK FROM CONNECTOR POSITION (SHARED WITH RD/WH.
STRIP VINYL SLEEVING APPROXIMATELY 1/4" TO EXPOSE WIRE AND
TWIST.

*REMOVE WHITE WIRE FROM CONNECTOR POSITION (SHARED WITH BLK/WH). STRIP AS ABOVE.

TAPE WH/BLK AND WH WIRES TOGETHER - WIRE TO WIRE - AND INSERT IN EMPTY PLACE IN CONNECTOR.

IF YOU HAVE ANY QUESTIONS, PLEASE LET US KNOW.

JERRY CURTIS, SERVICE DIVISION

POLYTONE MUSICAL INSTRUMENTS INC

* CUT

^{**} POSITION #5 is RED for MEGA BRUTE, BLACK for ALL OTHER MODELS